

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date : 2022/11/07
Version: 2.0

Page: 1/14
(30711122/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

WALLTITE CM01 RESIN

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry
Unsuitable for use: Uses other than recommended

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: resin
Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Corr./Irrit.	2	Skin corrosion/irritation
Skin Sens.	1	Skin sensitization

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 2/14

(30711122/SDS_GEN_US/EN)

Repr.	2 (unborn child)	Reproductive toxicity
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging the unborn child.
H373	May cause damage to organs (Kidney) through prolonged or repeated exposure (oral).
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe mist or vapour or spray.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P308 + P313	IF exposed or concerned: Get medical attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 3/14

(30711122/SDS_GEN_US/EN)

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Ethylenediamine, ethoxylated and propoxylated

CAS Number: 26316-40-5

Content (W/W): ≥ 15.0 - $< 20.0\%$

Synonym: (POLYMER) 1,2-Ethanediamine, polymer with 2-methyloxirane and oxirane

tris(2-chloro-1-methylethyl)phosphate

CAS Number: 13674-84-5

Content (W/W): ≥ 15.0 - $< 20.0\%$

Synonym: 1-Chloro-2-propanol phosphate (3:1); Tris (2-chloro-1-methylethyl)phosphate

Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

CAS Number: 940912-28-7

Content (W/W): ≥ 0.0 - $< 20.0\%$

Synonym: (POLYMER) Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Aromatic Amino Polyol

CAS Number: Trade Secret

Content (W/W): ≥ 0.0 - $< 20.0\%$

Synonym: No data available.

1-Propene, 1-chloro-3,3,3-trifluoro-, (1E)-

CAS Number: 102687-65-0

Content (W/W): ≥ 15.0 - $< 20.0\%$

Synonym: No data available.

diethylene glycol

CAS Number: 111-46-6

Content (W/W): ≥ 0.3 - $< 3.0\%$

Synonym: 2,2'-Oxybisethanol

2,2'-dimorpholinyl-diethylether

CAS Number: 6425-39-4

Content (W/W): ≥ 1.0 - $< 3.0\%$

Synonym: 2,2-Dimorpholinodiethyl ether

Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

CAS Number: 34354-45-5

Content (W/W): ≥ 0.0 - $< 3.0\%$

Synonym: (POLYMER) Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

Ethanol, 2,2',2'',2'''-(1,2-ethanediyldinitrilo)tetrakis-

CAS Number: 140-07-8

Content (W/W): ≥ 0.3 - $< 1.0\%$

Synonym: No data available.

Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07
Version: 2.0

Page: 4/14
(30711122/SDS_GEN_US/EN)

CAS Number: 67874-71-9
Content (W/W): $\geq 0.3 - < 1.0\%$
Synonym: No data available.

2-((2-(dimethylamino)ethyl)methylamino)ethanol
CAS Number: 2212-32-0
Content (W/W): $\geq 0.3 - < 1.0\%$
Synonym: 2-[[2-(Dimethylamino)ethyl]methylamino]ethanol

1,2-dimethylimidazole
CAS Number: 1739-84-0
Content (W/W): $\geq 0.2 - < 1.0\%$
Synonym: No data available.

C.I. Basic Violet
CAS Number: 72102-55-7
Content (W/W): $\geq 0.0 - < 0.1\%$
Synonym: Methylum, [4-(dimethylamino)phenyl]bis[4-(ethylamino)-3-methylphenyl]-, acetate

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Remove contact lenses, if present. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: corneal injury, skin irritation, Skin contact may provoke the following symptoms:, allergic symptoms, Ingestion may provoke the following symptoms:, kidney damage, Symptoms can appear later., Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Symptoms: Ingestion may cause gastrointestinal irritation with nausea, vomiting and diarrhea., skin irritation, corneal injury

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07
Version: 2.0

Page: 5/14
(30711122/SDS_GEN_US/EN)

Information on: Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide
Symptoms: skin irritation, corneal injury, Ingestion may cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Information on: 2,2'-dimorpholinyl-diethylether
Symptoms: Overexposure may cause: Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: tris(2-chloro-1-methylethyl)phosphate
Symptoms: Overexposure may cause: convulsions, depression, hypoxemia, tremors

Information on: diethylene glycol
Symptoms: Overexposure may cause: vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Hazards: Symptoms can appear later.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 6/14

(30711122/SDS_GEN_US/EN)

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Avoid inhalation of dusts/mists/vapours. When using do not eat, drink or smoke. Wear suitable gloves and eye/face protection. Protect against moisture.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 15 - 25 °C

Storage duration: 6 Months

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 7/14

(30711122/SDS_GEN_US/EN)

General safety and hygiene measures:

Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately. Do not eat, drink or use tobacco while working. Wash thoroughly after handling.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	amine-like	
Odour threshold:	No applicable information available.	
Colour:	Purple	
pH value:	≥ 7	
Freezing point:	No data available.	
Melting point:	No data available.	
Boiling point:	> 140 °C	
Sublimation point:	No applicable information available.	
Flash point:	> 94 °C	(closed cup)
Flammability:	not flammable	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 250 °C	
Vapour pressure:	< 0.1 hPa (25 °C)	
Density:	1.19 g/cm ³ (20 °C)	
Relative density:	No applicable information available.	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	slightly soluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	not applicable	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 8/14

(30711122/SDS_GEN_US/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral

Type of value: ATE

Value: > 2,317 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

No applicable information available.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 9/14

(30711122/SDS_GEN_US/EN)

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes irritation.

Information on: Ethylenediamine, ethoxylated and propoxylated

Assessment of irritating effects: Eye contact causes irritation.

Information on: Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: Aromatic Amino Polyol

Assessment of irritating effects: May cause severe damage to the eyes.

Information on: Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: 2,2'-dimorpholinyl-diethylether

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes slight irritation.

Information on: 2-((2-(dimethylamino)ethyl)methylamino)ethanol

Assessment of irritating effects: Corrosive! Damages skin and eyes.

Information on: Ethanol, 2,2',2'',2'''-(1,2-ethanediyldinitrilo)tetrakis-

Assessment of irritating effects: May cause severe damage to the eyes. Not irritating to the skin. Prolonged contact with the product can result in skin irritation.

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: 1,2-dimethylimidazole

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

May produce an allergic reaction.

Information on: Ethylenediamine, ethoxylated and propoxylated

Assessment of sensitization:

Sensitization after skin contact possible.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07
Version: 2.0

Page: 10/14
(30711122/SDS_GEN_US/EN)

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: diethylene glycol

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The effects were only observed at doses/concentrations not relevant for classification and/or practical use conditions. These effects are not relevant to humans at occupational levels of exposure.

The substance may cause damage to the liver after repeated ingestion.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Medical conditions aggravated by overexposure

Individuals with allergic history or pre-existing dermatitis should use extra precautions when handling this product. The substance may cause sensitization of the skin in particularly sensitive individuals.

12. Ecological Information

Toxicity

Aquatic toxicity

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 11/14

(30711122/SDS_GEN_US/EN)

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish

Information on: tris(2-chloro-1-methylethyl)phosphate

LC50 (96 h) 51 mg/l, Pimephales promelas (Fish test acute, static)

LC50 (96 h) 56 mg/l, Brachydanio rerio (Fish test acute, static)

Information on: C.I. Basic Violet

LC50 (48 h) 0.1 mg/l, Oryzias latipes (other)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LC50 (96 h) 0.1 mg/l, Oryzias latipes (JIS K 0102-71)

Literature data. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Aromatic Amino Polyol

LC50 (96 h) 1.07 mg/l (Flow through.)

Aquatic invertebrates

Information on: tris(2-chloro-1-methylethyl)phosphate

EC50 (48 h) 131 mg/l, Daphnia magna (Daphnia test acute, static)

The statement of the toxic effect relates to the analytically determined concentration.

Information on: C.I. Basic Violet

LC50 (72 h) 1.9 mg/l, other (other)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

EC50 (48 h) 0.05 mg/l, Daphnia magna (Directive 79/831/EEC, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Aromatic Amino Polyol

EC50 (48 h) 8.35 mg/l (Flow through.)

Aquatic plants

Information on: tris(2-chloro-1-methylethyl)phosphate

EC50 (72 h) 82 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)

Nominal concentration.

Information on: Aromatic Amino Polyol

No observed effect concentration (96 h) 0.0986 mg/l (static)

EC50 (96 h) 0.59 mg/l (static)

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07
Version: 2.0

Page: 12/14
(30711122/SDS_GEN_US/EN)

Information on: *tris(2-chloro-1-methylethyl)phosphate*

Information on: *C.I. Basic Violet*

:

No data available.

aerobic

activated sludge, industrial/EC20 (0.5 h): 4 mg/l

DIN 38412 Part 27 (draft) aerobic

bacterium/EC10 (0.5 h): 0.75 mg/l

Information on: *Aromatic Amino Polyol*

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system. Incinerate or dispose of in a licensed facility.

Container disposal:

Do not reuse empty containers. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove.

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07
Version: 2.0

Page: 13/14
(30711122/SDS_GEN_US/EN)

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

PA

CAS Number

111-46-6

50-00-0

Chemical name

diethylene glycol

Formaldehyde

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including FORMALDEHYDE (GAS), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 1 Special:

HMIS III rating

Health: 3 \square Flammability: 1 Physical hazard: 1

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2022/11/07

Safety Data Sheet

WALLTITE CM01 RESIN

Revision date: 2022/11/07

Version: 2.0

Page: 14/14

(30711122/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.

END OF DATA SHEET